

100% Italian diaphragm pressure tanks

Italian pressure tanks with diaphragm membrane

Temperature -10 +99 °C - Pre-charge pressure 2 bar

Standard Code	Capacity	Max. pressure	Connection	Dimensions	
	L	bar	inch	mm	
VERTICAL					
UD0083FUS4000000	8	8	1"	200	300
UD0192FUS4000000	19	10	3/4"	250	450
UD0193FUS4000000	19	10	1"	250	450
UD0193FUS416B000	19	16	1"	250	450
UD0242FUS4000000	24	10	3/4"	290	460
UD0243FUS4000000	24	10	1"	290	460
UD0402FUS4000000	40	10	3/4"	380	360
UD0403FUS4000000	40	10	1"	320	460
UD0603FUS4000000	60	10	1"	320	760
UD1003FUS4000000	100	10	1"	450	810
UD1403FUS4000000	140	10	1"	450	1025
UD2003FUS4000000	200	10	1"	550	1080
UD2803FUS4000000	280	10	1"	550	1385
UD430VFUS4000000	430	10	1"1/4	630	1625
HORIZONTAL					
UD0203FUS40BP000	20	10	1"	280	490
UD0613FUS4000000	60	10	1"	430	670
UD1013FUS4000000	100	10	1"	485	700

butyl
diaphragm

high resistance
painting

synthetic
internal soft
liner

stainless steel
connection